

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No.

95-424

First Named Inventor or
Application Identifier:

Lockwood

Title: Arrangement for Converting Telephone Number Formats for
Notification Systems

(Only for new nonprovisional applications under 37 CFR 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent
application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☐ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 13]
3. ☒ Formal Drawing(s) (35 USC 113) [Total Sheets: 2]
4. ☐ Oath or Declaration [Total Pages:]
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under
Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, status still proper and desired.
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: /

18. CORRESPONDENCE ADDRESS

Leon R. Turkevich, Esq.
CUSTOMER NO.: 23164
2000 M Street, N.W., 7th Floor
Washington, D.C. 20036-3307

Name (Type) Leon R. Turkevich

Registration No.
(Att./Agent)

34,035

Signature

Date

June 29, 2000

06/29/00
jc803 U.S. PTO

06/29/00
jc803 U.S. PTO

jc856 U.S. PTO
09/605855
06/29/00

Year	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

1

FOR

INVENTOR:

PREPARED BY:

Leon R. Turkevich, Esq.
2000 M STREET, N.W., 7th Floor
WASHINGTON, D.C. 20036-3307
(202) 261-1059

ARRANGEMENT FOR CONVERTING TELEPHONE NUMBER FORMATS FOR NOTIFICATION SYSTEMS

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to message notification systems configured for sending a notification message to a subscriber's destination telephone number.

DESCRIPTION OF THE RELATED ART

5 Short Message Services (SMS) have been implemented in wireless telephone communications systems as a way to send a message to a subscriber's cellular phone to notify the subscriber that he or she has received a new voice mail. A messaging server, also referred to as a Short Message Service Center (SMSC), is configured for receiving a notification message from a messaging source according to Short Message Peer to Peer Protocol (SMPP). The messaging source may be, for example, a voice mail system, a paging system, or an e-mail interface resident within the wireless telephone communications system. The SMSC, in response to receiving the notification message from the messaging source, transmits a short message to the cellular phone based on the destination telephone number specified within the notification message.

Unified communications systems are under development as a way of enhancing messaging services for users such as wireless telephone subscribers. A disadvantage of unified communications systems implemented as enhanced versions of the voice mail system, paging system, or e-mail interface resident within the wireless telephone communications system is that such implementation requires detailed knowledge of the proprietary protocols associated with the voice mail systems. Hence, such implementations are available only from switch vendors having knowledge of the proprietary protocols.

Use of a unified communications system implemented independent of the existing proprietary voice mail systems enables service providers to use scalable and distributed systems using recognized communication protocols. Hence, the service providers may use such unified communications systems across multiple platforms, independent of protocol.

25 One disadvantage of the independent-type unified communications systems is compatibility between the unified communications system and the hardware deployed by the service provider. For

example, a problem may arise if the unified communications system is configured for storing telephone numbers in one format (e.g., a national format), while the SMSC receiving the notification messages from the unified communications system is configured for utilizing telephone numbers in a different format (e.g., international format).

5

SUMMARY OF THE INVENTION

There is a need for an arrangement that resolves incompatibilities between telephone formats between a notification system and a messaging server, without the necessity of reconfiguring the telephone format within the notification system or the messaging server.

10

These and other needs are attained by the present invention, where a notification system includes a dial map configured for converting the destination telephone number within a notification message from an original format to another format recognizable by a messaging server, based on execution of a mapping rule selected based on a match between the mapping rule and the destination telephone number having the original format.

20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990

One aspect of the present invention provides a method in a notification system for sending a notification message for a user to a messaging server configured for identifying the user based on a destination telephone number in a first format. The method includes obtaining for the notification message a destination telephone number in a second format. The method also includes converting the destination telephone number in the second format to the destination telephone number in the first format based on execution of a mapping rule selected based on a match between the mapping rule and at least a portion of the destination telephone number in the second format. The notification message is then output having the destination telephone number having the first format. Converting the destination telephone number based on mapping rules enables user-defined pattern matching rules instead of number-specific conversions. Hence, the system can be programmed for different phone formats, providing flexibility for deployment.

25

Another aspect of the present invention provides a notification system configured for sending a notification message for a user to a messaging server, the messaging server configured for identifying the user based on a destination telephone number in a first format. The notification system includes a message interface configured for receiving the notification message and having

the destination telephone number in a second format, a dial map and an output interface. The dial map is configured for converting the destination telephone number in the second format to the destination telephone number in the first format, the dial map executing a selected mapping rule based on a match between the mapping rule and at least a portion of the destination telephone number in the second format. The output interface is configured for outputting to the messaging server the notification message having the destination telephone number in the first format

Additional advantages and novel features of the invention will be set forth in part in the description which follows and in part will become apparent to those skilled in the art upon examination of the following or may be learned by practice of the invention. The advantages of the present invention may be realized and attained by means of instrumentalities and combinations particularly pointed out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Reference is made to the attached drawings, wherein elements having the same reference numeral designations represent like elements throughout and wherein:

Figure 1 is a diagram of a system utilizing a notification system and a messaging server for supplying a notification message to a user.

Figure 2 is a diagram illustrating in detail the notification system of Figure 1.

Figure 3 is a diagram illustrating a mapping rule configured for converting telephone number formats according to an embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Figure 1 is a diagram of a system utilizing a notification system and a messaging server for supplying a notification message to a user according to an embodiment of the present invention. The notification system 10 is preferably implemented as a web-based unified communications system configured for storing and managing voice, e-mail, or facsimile messages using an open standards architecture (e.g., Internet protocol). An example of the notification system 10 is the commercially-available uOne Unified Messaging System (Version 4.1) from Cisco Systems, Inc., San Jose, California.

The notification system 10 is configured for sending a notification message 12 to the messaging server 14, illustrated as an SMSC, via SMPP protocol. As recognized in the art, the SMSC 14 is configured for sending a wireless message 16 to a user's cellphone 18 based on the destination telephone number specified within the notification message 12.

According to the disclosed embodiment, a telephone number conversion module 20 is added to the notification system 10 to ensure that the notification message 12 sent to the messaging server 14 includes a destination telephone number that has a format recognizable by the messaging server 14. In particular, a service provider may need to store telephone numbers within the notification system 10 in one format (e.g., a country-specific format), even though the SMSC 14 is configured for processing SMPP messages according to another format (e.g., an international format that specifies a country code). Hence, the telephone number conversion module 20 is configured for converting the destination telephone number within the notification message from the country-specific format to the international format, eliminating the necessity for reprogramming of the notification system 10 with telephone numbers to match the requirements of the SMSC 14.

Figure 2 is a diagram illustrating in detail the telephone number conversion module 20 configured for executing selected mapping rules, illustrated in Figure 3, according to an embodiment of the present invention. The operations described with respect to Figures 2 and 3 can be implemented as executable code that is stored on a computer readable medium (e.g., a hard disk drive, a floppy drive, a random access memory, a read only memory, an EPROM, a compact disk, etc).

The telephone number conversion module 20 includes a message interface 22 configured for receiving the notification message 12a generated by the notification system 10. In particular, the notification message 12a received by the message interface 22 includes source and destination telephone numbers in the format utilized by the notification system 10, for example a national-type, country-specific format such as the Numbering Plan Area (NPA) format utilized in the United States. The telephone number conversion module 20 also includes a dial map 24, for example an executable resource executed by a computer-based system, configured for converting the telephone numbers in the received notification message 12a into a format recognizable by the SMSC 14, for example an international format. As described in further detail below with respect to Figure 3, the dial map

24 selects from a plurality of mapping rules 30 stored, for example, in a database 26. Once the dial map 24 converts the telephone numbers in the received notification message 12a into the format recognizable by the SMSC 14, an output interface 28 in the telephone number conversion module 20 outputs the converted notification message 12b having the converted telephone numbers to the SMSC 14 according to SMPP protocol.

Figure 3 is a diagram illustrating in detail an exemplary mapping rule configured for converting a telephone number from a first telephone number format to another prescribed telephone number format according to an embodiment of the present invention. The mapping rule is implemented by specifying a regular expression term 32, illustrated as the term "804762([0-9]4)\$0", within at least one field 34. The regular expression term 32 within the destination telephone number field 34a includes a prescribed telephone number pattern 32a (e.g., "804762") that is used by the dial map 24 to determine if there is a match between a telephone number and the corresponding mapping rule 30. The regular expression term 32 also includes an operand 32b "([0-9]4)" that specifies the nature of the comparison with the prescribed pattern 32a and a field identifier 32c (e.g., "\$0"). In particular, the illustrated operand 32b specifies that the dial map 24 can accept any digits from 0 to 9, with up to four digits remaining; hence, the term 32 will match any telephone number that starts with "804 762", and that has four more digits.

As illustrated in Figure 3, the source telephone number field 34b has an asterisk (*), indicating a don't care for the comparison by the dial map 24.

The return field 34c specifies the second number format to be utilized for the outgoing notification message 12b, and includes format-specific digits 36 ("1 21 804 555") and a string identifier 38 ("ST0"), which references identifier 0 in the To: field, i.e., the last four digits of the incoming message 12a. Hence, the mapping rule 30 would convert the telephone number "804 762 0000" from the NPA format to the international format "1 21 804 555 0000".

As apparent from the foregoing, the dial map 24 searches for a match between the destination telephone number within the received notification message 12a and the mapping rules 30 stored in the database 26, and executes a selected mapping rule 30 based on a match between the mapping rule and at least a portion of the destination telephone number in the received notification message 12a. Hence, multiple rules may be implemented for different telephone numbers, enabling the conversion

of numbers to different formats depending on the number prefixes. Hence, the dial map 24 may access different mapping rules 30, enabling the messaging server 14 to serve multiple countries having respective telephone number formats.

While this invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is Claimed Is:

1. A method in a notification system for sending a notification message for a user to a messaging server configured for identifying the user based on a destination telephone number in a first format, the method including:

obtaining for the notification message a destination telephone number in a second format;

5 converting the destination telephone number in the second format to the destination telephone number in the first format based on execution of a mapping rule selected based on a match between the mapping rule and at least a portion of the destination telephone number in the second format; and outputting the notification message having the destination telephone number having the first format.

2. The method of claim 1, wherein the outputting step includes outputting the notification message to the messaging server according to Short Message Peer to Peer (SMPP) protocol.

3. The method of claim 2, wherein the messaging server is a Short Message Service Center configured for sending the notification message to a wireless telephone corresponding to the destination telephone number having the first format.

4. The method of claim 3, wherein the first format is an international telephone format, and the second format is a national telephone format.

5. The method of claim 4, wherein the converting step includes matching the mapping rule and the at least a portion of the destination telephone number in the second format based on a prescribed pattern within the destination telephone number in the second format.

6. The method of claim 5, wherein the matching step includes determining the prescribed pattern from a specified regular expression, within the matched mapping rule, that specifies the prescribed pattern.

7. The method of claim 6, wherein the converting step further includes replacing the at least a portion of the destination telephone number in the second format with a replacement value specified in the matched mapping rule.

8. The method of claim 1, wherein the converting step includes matching the mapping rule and the at least a portion of the destination telephone number in the second format based on a prescribed pattern within the destination telephone number in the second format.

9. The method of claim 8, wherein the matching step includes determining the prescribed pattern from a specified regular expression, within the matched mapping rule, that specifies the prescribed pattern.

10. The method of claim 9, wherein the converting step further includes replacing the at least a portion of the destination telephone number in the second format with a replacement value specified in the matched mapping rule.

11. The method of claim 10, wherein the first format is an international telephone format, and the second format is a national telephone format.

12. A notification system configured for sending a notification message for a user to a messaging server, the messaging server configured for identifying the user based on a destination telephone number in a first format, the notification system including:

a message interface configured for receiving the notification message and having the destination telephone number in a second format;

a dial map configured for converting the destination telephone number in the second format to the destination telephone number in the first format, the dial map executing a selected mapping rule based on a match between the mapping rule and at least a portion of the destination telephone number in the second format; and

a output interface configured for outputting to the messaging server the notification message

having the destination telephone number in the first format.

13. The system of claim 12, wherein the output interface is configured for outputting the notification message according to Short Message Peer to Peer (SMTP) protocol.

14. The system of claim 12, wherein the dial map is configured for storing a plurality of the mapping rules, each mapping rule specifying a corresponding first expression, and a corresponding to second expression having the first format, the dial map selecting the selected mapping rule based on a match between the destination telephone number having the second format and the corresponding first expression.

15. The system of claim 14, wherein the dial map selects the selected mapping rule based on the corresponding first expression specifying a regular expression having a specified pattern that matches the at least a portion of the destination telephone number having the second format.

16. A computer readable medium having stored thereon sequences of instructions for sending a notification message for a user to a messaging server configured for identifying the user based on a destination telephone number in a first format, the sequences of instructions including instructions for performing the steps of:

obtaining for the notification message a destination telephone number in a second format;

converting the destination telephone number in the second format to the destination telephone number in the first format based on execution of a mapping rule selected based on a match between the mapping rule and at least a portion of the destination telephone number in the second format; and

outputting the notification message having the destination telephone number having the first format.

17. The medium of claim 16, wherein the outputting step includes outputting the notification message to the messaging server according to Short Message Peer to Peer (SMPP) protocol.

18. The medium of claim 17, wherein the messaging server is a Short Message Service Center configured for sending the notification message to a wireless telephone corresponding to the destination telephone number having the first format.

19. The medium of claim 18, wherein the first format is an international telephone format, and the second format is a national telephone format.

20. The medium of claim 19, wherein the converting step includes matching the mapping rule and the at least a portion of the destination telephone number in the second format based on a prescribed pattern within the destination telephone number in the second format.

21. The medium of claim 20, wherein the matching step includes determining the prescribed pattern from a specified regular expression, within the matched mapping rule, that specifies the prescribed pattern.

22. The medium of claim 21, wherein the converting step further includes replacing the at least a portion of the destination telephone number in the second format with a replacement value specified in the matched mapping rule.

23. The medium of claim 16, wherein the converting step includes matching the mapping rule and the at least a portion of the destination telephone number in the second format based on a prescribed pattern within the destination telephone number in the second format.

24. The medium of claim 23, wherein the matching step includes determining the prescribed pattern from a specified regular expression, within the matched mapping rule, that specifies the prescribed pattern.

25. The medium of claim 24, wherein the converting step further includes replacing the at least a portion of the destination telephone number in the second format with a replacement value

specified in the matched mapping rule.

26. The medium of claim 25, wherein the first format is an international telephone format, and the second format is a national telephone format.

27. A notification system configured for sending a notification message for a user to a messaging server, the messaging server configured for identifying the user based on a destination telephone number in a first format, the notification system including:

a message interface configured for receiving the notification message and having the destination telephone number in a second format;

means for converting the destination telephone number in the second format to the destination telephone number in the first format, the converting means executing a selected mapping rule based on a match between the mapping rule and at least a portion of the destination telephone number in the second format; and

an output interface configured for outputting to the messaging server the notification message having the destination telephone number in the first format.

28. The system of claim 27, wherein the output interface is configured for outputting the notification message according to Short Message Peer to Peer (SMTP) protocol.

29. The system of claim 27, wherein the converting means is configured for storing a plurality of the mapping rules, each mapping rule specifying a corresponding first expression, and a corresponding to second expression having the first format, the dial map selecting the selected mapping rule based on a match between the destination telephone number having the second format and the corresponding first expression.

30. The system of claim 29, wherein the converting means selects the selected mapping rule based on the corresponding first expression specifying a regular expression having a specified

95-424

Figure 1





Figure 2






Figure 3